

Пескоразбрасыватели SP-100-1, SP-125-1, SP-225-1, SR-210 Технические характеристики



По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Россия (495)268-04-70

Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Казахстан (7172)727-132

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

SIMPLE, PLUG-AND-PLAY OPERATION

Spreaders that can quickly connect to many different types of vehicles, with specific models catering to various bagged deicing materials.

CONSISTENT MATERIAL DELIVERY

The 3-inch vertical high-flow auger allows for efficient spreading of bagged rock salt and calcium flake.

SEALED DRIVE ENCLOSURE

Electric-powered spinner motor transmission is contained in a sealed, weather-resistant enclosure.

ELECTRIC GATE SP-100-1

Starts and stops material flow to the spinner for better material control and less waste.

VARIABLE-SPEED CONTROL

Weather-resistant, cab-mounted control allows for spinner speed adjustment. Standard on SP-100-1/SP-325. Optional on SP-125-1/SP-225-1.

ADDITIONAL FEATURES

Weather Cover (SP-100-1), Fitted Lid (SP-325), Standard Receiver Mount

MODEL:	SP-100-1	SP-125-1	SP-225-1	SP-325	SR-210
Capacity (Volume)	3.0 cu ft	3.0 cu ft	3.0 cu ft	3.25 cu ft	3.0 cu ft
Capacity (Weight)	240 lb	240 lb	240 lb	260 lb	240 lb
Empty Weight	75 lb	65 lb	68 lb	79 lb	68 lb



ALL UTILITY & WIRELESS UTILITY SPREADERS

UTILITY MOUNT

Installs spreaders to the back of utility vehicles.



3-POINT MOUNT

Adds spreaders to the 3-point hitch of utility tractors.



DROP UTILITY MOUNT

Provides a lower-profile mount for utility vehicles.



SP-125-1/SP-225-1/SR-210

PIVOT PAL

Allows tailgate spreaders to swing away from tailgate.



SP-125-1

20' MANUAL GATE CABLE KIT



SP-125-1/SP-225-1

WEATHER-RESISTANT CONTROL



SR-210

WIRELESS SPREADER HARNESS



SP-125-1/SP-225-1/SR-210

WEATHER COVER



WIRELESS CONTROL SR-210

A pocket-sized, wireless key fob offers two spinner speed settings for easy operation.



See Pages 28-30 for full list of accessories.

Utility Specifications

Construction

Imperial	SP-100-1	SP-125-1	SP-225-1	SP-325
Frame	Powder coated steel	Powder coated steel	Powder coated steel	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly
Motors	12-volt DC motor mounted in weather resistant enclosure	12-volt DC motor mounted in weather resistant enclosure	12-volt DC motor mounted in weather resistant enclosure	12-volt DC motor mounted in weather resistant enclosure
Spinner Drive Assembly	Maximum torque transmission with hardened-steel worm and bronze gear	Maximum torque transmission with hardened-steel worm and bronze gear	Maximum torque transmission with hardened-steel worm and bronze gear	Maximum torque transmission with hardened-steel worm and bronze gear
Spinner	10" nylon/glass reinforced resin	10" nylon/glass reinforced resin	10" nylon/glass reinforced resin	10" nylon/glass reinforced resin
Auger	N/A	N/A	3" vertical high-flow auger	3" vertical high-flow auger
Mounting	2" light-duty hitch mount is standard	2" light-duty hitch mount is standard	2" light-duty hitch mount is standard	2" light-duty hitch mount is standard

Metric	SP-100-1	SP-125-1	SP-225-1	SP-325
Frame	Powder coated steel	Powder coated steel	Powder coated steel	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly
Motors	12-volt DC motor mounted in weather resistant enclosure	12-volt DC motor mounted in weather resistant enclosure	12-volt DC motor mounted in weather resistant enclosure	12-volt DC motor mounted in weather resistant enclosure
Spinner Drive Assembly	Maximum torque transmission with hardened-steel worm and bronze gear	Maximum torque transmission with hardened-steel worm and bronze gear	Maximum torque transmission with hardened-steel worm and bronze gear	Maximum torque transmission with hardened-steel worm and bronze gear
Spinner	25.4 cm nylon/glass reinforced resin	25.4 cm nylon/glass reinforced resin	25.4 cm nylon/glass reinforced resin	25.4 cm nylon/glass reinforced resin
Auger	N/A	N/A	7.6 cm vertical high-flow auger	7.6 cm vertical high-flow auger
Mounting	5.1 cm light-duty hitch mount is standard	5.1 cm light-duty hitch mount is standard	5.1 cm light-duty hitch mount is standard	5.1 cm light-duty hitch mount is standard

Dimensions

Imperial	SP-100-1	SP-125-1	SP-225-1	SP-325
Approx. Weight (Empty)	75 lb	65 lb	68 lb	79 lb
Overall Length	22"	22"	22"	18"
Overall Height	30"	30"	32"	33"
Overall Width	30"	30"	30"	33"
Hopper Length	22"	22"	22"	16.5"
Hopper Width	30"	30"	30"	33"

Utility Specifications

Metric	SP-100-1	SP-125-1	SP-225-1	SP-325
Approx. Weight (Empty)	34.0 kg	29.5 kg	30.8 kg	35.8 kg
Overall Length	55.9 cm	55.9 cm	55.9 cm	45.7 cm
Overall Height	76.2 cm	76.2 cm	81.3 cm	83.8 cm
Overall Width	76.2 cm	76.2 cm	76.2 cm	83.8 cm
Hopper Length	55.9 cm	55.9 cm	55.9 cm	41.9 cm
Hopper Width	76.2 cm	76.2 cm	76.2 cm	83.8 cm

Electrical

Imperial	SP-100-1	SP-125-1	SP-225-1	SP-325
Speed Control	Weather-resistant variable speed control	On/off switch	On/off switch	Weather-resistant variable speed control
Wiring Harness	12-gauge with molded plugs and connectors	Multiple gauge harness with plug-ends and finished connectors	Automotive style with plug-ends and finished connectors	Completely loomed with molded plugs

Metric	SP-100-1	SP-125-1	SP-225-1	SP-325
Speed Control	Weather-resistant variable speed control	On/off switch	On/off switch	Weather-resistant variable speed control
Wiring Harness	12-gauge with molded plugs and connectors	Multiple gauge harness with plug-ends and finished connectors	Automotive style with plug-ends and finished connectors	Completely loomed with molded plugs

Operational

Imperial	SP-100-1	SP-125-1	SP-225-1	SP-325
Capacity (Volume)	3.0 cu ft	3.0 cu ft	3.0 cu ft	3.25 cu ft
Capacity (Weight)*	240 lb	240 lb	240 lb	260 lb
Spreading Width	Up to 20'	Up to 20'	Up to 25'	Up to 25'

Metric	SP-100-1	SP-125-1	SP-225-1	SP-325
Capacity (Volume)	0.085 cu m	0.085 cu m	0.085 cu m	0.092 cu m
Capacity (Weight)*	108.9 kg	108.9 kg	108.9 kg	117.9 kg
Spreading Width	Up to 6.1 m	Up to 6.1 m	Up to 7.6 m	Up to 7.6 m

Standard Equipment

Imperial	SP-100-1	SP-125-1	SP-225-1	SP-325
Cover	Standard	Optional	Optional	Fitted lid
Feedgate	Electronically Controlled	Manual	Manual	Manual

Metric	SP-100-1	SP-125-1	SP-225-1	SP-325
Cover	Standard	Optional	Optional	Fitted lid
Feedgate	Electronically Controlled	Manual	Manual	Manual

Utility Specifications

Construction

Imperial	SR-210
Frame	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly
Motors	12-volt DC motor mounted in weather resistant enclosure
Spinner Drive Assembly	Maximum torque transmission with hardened-steel worm and bronze gear
Spinner	10" nylon/glass reinforced resin
Auger	3" vertical high-flow auger
Mounting	2" light-duty hitch mount is standard

Metric	SR-210
Frame	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly
Motors	12-volt DC motor mounted in weather resistant enclosure
Spinner Drive Assembly	Maximum torque transmission with hardened-steel worm and bronze gear
Spinner	25.4 cm nylon/glass reinforced resin
Auger	7.6 cm vertical high-flow auger
Mounting	5.1 cm light-duty hitch mount is standard

Dimensions

Imperial	SR-210
Approx. Weight (Empty)	68 lb
Overall Length	22"
Overall Height	32"
Overall Width	30"
Hopper Length	22"
Hopper Width	30"

Metric	SR-210
Approx. Weight (Empty)	30.8 kg
Overall Length	55.9 cm
Overall Height	81.3 cm
Overall Width	76.2 cm
Hopper Length	55.9 cm
Hopper Width	76.2 cm

Electrical

Imperial	SR-210
Speed Control	On/off with 2 pre-set spinner speeds on a wireless controlled key fob
Wiring Harness	7-pin plug-to-plug in trailer outlet on hitch, no harness required

Utility Specifications

Metric	SR-210
Speed Control	On/off with 2 pre-set spinner speeds on a wireless controlled key fob
Wiring Harness	7-pin plug-to-plug in trailer outlet on hitch, no harness required

Operational

Imperial	SR-210
Capacity (Volume)	3.0 cu ft
Capacity (Weight)*	240 lb
Spreading Width	Up to 25'

Metric	SR-210
Capacity (Volume)	0.085 cu m
Capacity (Weight)*	108.9 kg
Spreading Width	Up to 7.6 m

Standard Equipment

Imperial	SR-210
Cover	Optional

Metric	SR-210
Cover	Optional

Wireless Utility Specifications

Construction

Imperial	SR-210
Frame	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly
Motors	12-volt DC motor mounted in weather resistant enclosure
Spinner Drive Assembly	Maximum torque transmission with hardened-steel worm and bronze gear
Spinner	10" nylon/glass reinforced resin
Auger	3" vertical high-flow auger
Mounting	2" light-duty hitch mount is standard

Metric	SR-210
Frame	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly
Motors	12-volt DC motor mounted in weather resistant enclosure
Spinner Drive Assembly	Maximum torque transmission with hardened-steel worm and bronze gear
Spinner	25.4 cm nylon/glass reinforced resin
Auger	7.6 cm vertical high-flow auger
Mounting	5.1 cm light-duty hitch mount is standard

Dimensions

Imperial	SR-210
Approx. Weight (Empty)	68 lb
Overall Length	22"
Overall Height	32"
Overall Width	30"
Hopper Length	22"
Hopper Width	30"

Metric	SR-210
Approx. Weight (Empty)	30.8 kg
Overall Length	55.9 cm
Overall Height	81.3 cm
Overall Width	76.2 cm
Hopper Length	55.9 cm
Hopper Width	76.2 cm

Electrical

Imperial	SR-210
Speed Control	On/off with 2 pre-set spinner speeds on a wireless controlled key fob
Wiring Harness	7-pin plug-to-plug in trailer outlet on hitch, no harness required

Wireless Utility Specifications

Metric	SR-210
Speed Control	On/off with 2 pre-set spinner speeds on a wireless controlled key fob
Wiring Harness	7-pin plug-to-plug in trailer outlet on hitch, no harness required

Operational

Imperial	SR-210
Capacity (Volume)	3.0 cu ft
Capacity (Weight)*	240 lb
Spreading Width	Up to 25'

Metric	SR-210
Capacity (Volume)	0.085 cu m
Capacity (Weight)*	108.9 kg
Spreading Width	Up to 7.6 m

Standard Equipment

Imperial	SR-210
Cover	Optional

Metric	SR-210
Cover	Optional

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Россия (495)268-04-70

Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Казахстан (7172)727-132

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93