

Пескоразбрасыватели SP-575X-1, SP-1075X-1

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Россия (495)268-04-70

Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Казахстан (7172)727-132

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Tailgate Pro

FLEETFLEX
ELECTRICAL SYSTEM

**TAILGATE
SPREADERS**



FEATURES & SPECIFICATIONS

VERTICAL HIGH-FLOW AUGER

The 3-inch high-flow auger allows the units to spread bagged rock salt and calcium flake consistently.

PATENTED SEALED DRIVE ENCLOSURE

Protects 12-volt electric drive/transmission from the elements for longer spreader life.

FITTED LID

The fitted lid provides a convenient solution to protect material from moisture.

STANDARD RECEIVER MOUNT

SP-575X-1

Model SP-575X-1 comes standard with a 2-inch (51 mm) receiver mount, making it ideal for use on a variety of vehicles. Model SP-1075X-1 offers plenty of versatility with optional receiver, pivot and 3-point mounting systems available.

VARIABLE-SPEED DIGITAL CONTROL

The compact digital control offers variable-speed control of the spinner. It features a diagnostic display, bright LED lights and convenient accessory buttons for easy control of optional accessories.

ADDITIONAL FEATURES: Single-Stage Design (1 auger)



MODEL:	SP-575X-1	SP-1075X-1
Capacity Volume	5.75 cu ft	10.75 cu ft
Capacity Weight	460 lb	860 lb
Empty Weight	106 lb	141 lb

OPTIONAL MOUNTS

SP-575X-1

PIVOT PAL

Allows tailgate spreaders to swing away from tailgate.



SP-1075X-1

UNIVERSAL PIVOT MOUNT

Allows tailgate spreaders to swing away from tailgate. Height, width, bumper style and tailgate offset are adjustable to different trucks.



ACCESSORIES

WORK LIGHT



ADJUSTABLE DEFLECTOR



See Pages 28-30 for full list of accessories.

Tailgate Pro Specifications

Construction

Imperial	SP-575X-1	SP-1075X-1
Frame	Powder coated steel	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly
Motors	12-volt DC motor mounted in weather resistant enclosure	12-volt DC motor mounted in weather resistant enclosure
Spinner Drive Assembly	Maximum torque transmission with hardened-steel worm and bronze gear	Maximum torque transmission with hardened-steel worm and bronze gear
Spinner	10" nylon/glass reinforced resin	10" nylon/glass reinforced resin
Auger	3" vertical high-flow auger	3" vertical high-flow auger
Mounting	Receiver mount standard. Other mounts optional.	Mount not included. (Receiver, 3-point or pivot mount optional)

Metric	SP-575X-1	SP-1075X-1
Frame	Powder coated steel	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly
Motors	12-volt DC motor mounted in weather resistant enclosure	12-volt DC motor mounted in weather resistant enclosure
Spinner Drive Assembly	Maximum torque transmission with hardened-steel worm and bronze gear	Maximum torque transmission with hardened-steel worm and bronze gear
Spinner	25.4 cm nylon/glass reinforced resin	25.4 cm nylon/glass reinforced resin
Auger	7.6 cm vertical high-flow auger	7.6 cm vertical high-flow auger
Mounting	Receiver mount standard. Other mounts optional.	Mount not included. (Receiver, 3-point or pivot mount optional)

Dimensions

Imperial	SP-575X-1	SP-1075X-1
Approx. Weight (Empty)	106 lb	141 lb
Overall Length	20.5"	21"
Overall Height	35"	40"
Overall Width	38"	52"
Hopper Length	20.5"	21"
Hopper Width	38"	47.5"

Metric	SP-575X-1	SP-1075X-1
Approx. Weight (Empty)	48.1 kg	63.9 kg
Overall Length	52.1 cm	53.3 cm
Overall Height	88.9 cm	101.6 cm
Overall Width	96.5 cm	132.1 cm
Hopper Length	52.1 cm	53.3 cm
Hopper Width	96.5 cm	120.7 cm

Electrical

Imperial	SP-575X-1	SP-1075X-1
-----------------	------------------	-------------------

Tailgate Pro Specifications

Speed Control	Digital, self diagnosing variable speed control	Digital, self diagnosing variable speed control
Wiring Harness	Completely loomed with molded plugs	Completely loomed with molded plugs

Metric	SP-575X-1	SP-1075X-1
Speed Control	Digital, self diagnosing variable speed control	Digital, self diagnosing variable speed control
Wiring Harness	Completely loomed with molded plugs	Completely loomed with molded plugs

Operational

Imperial	SP-575X-1	SP-1075X-1
Capacity (Volume)	5.75 cu ft	10.75 cu ft
Capacity (Weight)*	460 lb	860 lb
Spreading Width	Up to 40'	Up to 40'

Metric	SP-575X-1	SP-1075X-1
Capacity (Volume)	0.163 cu m	0.304 cu m
Capacity (Weight)*	208.7 kg	390.1 kg
Spreading Width	Up to 12.2 m	Up to 12.2 m

Standard Equipment

Imperial	SP-575X-1	SP-1075X-1
Top Screen	1/4" steel rod construction with grid pattern	1/4" steel rod construction with grid pattern
Cover	Fitted lid	Fitted lid
Vibrator	Optional	Optional

Metric	SP-575X-1	SP-1075X-1
Top Screen	0.6 cm steel rod construction with grid pattern	0.6 cm steel rod construction with grid pattern
Cover	Fitted lid	Fitted lid
Vibrator	Optional	Optional

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Россия (495)268-04-70

Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Казахстан (7172)727-132

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93